

# WI-760 Laser Barcode Scanner



## General

WI-760 is one of our handheld barcode readers with manual and auto-sensor mode for your choice, its high cost-effective performance makes it ideal for supermarket, retail store, logistic and pharmacy systems.

## Technical Specifications

CPU	32Bits
Voltage:	DC 3.5-5.5V
Current:	50mA (working); 25mA (standby); 100mA (peak)
Interfaces	USB-HID, USB-UART, HID-POS, RS232, PS/2
Dimension:	166mmL x 63mmW x 88mmH
Weight:	175g

Light Source:	650nm±10% VLD
Depth of Field:	0-100cm
Revolve Angle:	±70° Left-right, ±70° Up-down
Print Contrast:	>=30%
Resolution:	>=4mil
Scan Rate:	200 scans per second
Bit Error Rate:	1/8 million
ESD Protect:	15KV
Dustproof and waterproof:	IP54
Operating Temperature:	-10°C ~ 50°C
Storage Temperature:	-20°C ~ 60°C
Humidity:	5% ~ 95% RH (non-condensing)
Decode type:	EAN/JAN-8,13 UPC-A; UPC-E; CODE-128; CODE-93;
	RSS-Standard, Limited, Expanded; CODE-39; Inter-Leaved 2/5;
	Standard 2/5; Matrix 2/5; Industrial 2/5; China-Post; MSI;